



# Alternate Maintenance Guide for TOLI Vinyl Flooring

JohnsonDiversey® WiWax™ is a neutral pH cleaner maintainer that contains a small amount of finish that remains to protect and restore the floor. When properly used, it will provide a satin gloss level that does not require buffing or stripping.

## Safety Precautions

- ❖ When performing any wet maintenance, always use wet floor signs and caution tape. Remove when finished.
- ❖ Carefully follow each product's label instructions and MSDS for proper use and personal protective equipment.



## Newly Installed Floor Care

- ❖ Permit light foot traffic immediately with pressure sensitive adhesive. Wait 3-4 hours after initial set for other adhesives.
- ❖ Keep furniture, fixtures and rolling traffic off the new floor for 48 hours.
- ❖ Always use plywood or other boards when moving heavy objects across the floor.
- ❖ Remove adhesive residue with a clean white cloth dampened with mineral spirits. Do not use AFTA.
- ❖ Sweep, dust mop or vacuum to remove all loose dirt and grit. Lightly damp mop with well rung mop as needed.
- ❖ Wait 72 hours (3 days) before wet cleaning the new floor. This will allow the adhesive to fully cure.

## Initial Maintenance

- ❖ Sweep, dust mop or vacuum to remove all loose dirt and grit. Do not use treated dust mops.
- ❖ Mix solution of JohnsonDiversey Profi™ (6-10 oz./gal.) in warm water and apply using mop or auto scrubber with 3M® 5100 **Red pad** (or equal). Let solution stand for 5-10 minutes and machine scrub. Do not let solution dry on the floor.
- ❖ Completely remove cleaning solution, rinse the floor thoroughly with clean water and allow to dry.
- ❖ Apply **2-3 coats of undiluted Wiwax™** following label instructions. Apply up to 4 coats for increased gloss and durability.
- ❖ Allow each coat to air dry completely (generally 30-60 minutes) before applying the next coat.

## Routine Maintenance (Daily or as needed)

- ❖ Sweep, dust mop or vacuum to remove all loose dirt and grit. Do not use treated dust mops.
- ❖ Mix solution of **WiWax™** (2 - 4 oz. /gal.) and apply with mop or auto scrubber using a 3M 5100 **Red pad** (or equal).
- ❖ Remove solution with a wet-vac or auto scrubber and allow the floor to dry.

## Periodic Deep Cleaning

- ❖ **To increase the shine, buff** the clean WiWax coated floor with a 175 rpm machine using a **White or Buffing pad**.
- ❖ **To remove scuffs, buff** the clean WiWax coated floor with a 175 rpm machine using a 3M 5100 **Red pad** (or equal).
- ❖ **To remove black marks, machine scrub** the floor with **Profi cleaner solution** (4 oz. /gal.) in warm water. Use a 3M 5300 **Blue pad** (or equal). Completely remove the solution, rinse the floor thoroughly with clean water and allow to dry.
- ❖ **To restore alcohol based hand sanitizer spots and dull or worn finish**, apply additional **undiluted coat of WiWax** in the affected areas with microfiber applicator. Follow label instructions.
- ❖ **Stripping Procedure** (Optional): Mix solution of JohnsonDiversey Linosafe™ following label instructions and machine scrub using a 3M 5300 **Blue pad** (or equal). Completely remove solution, rinse with clean water and allow floor to dry.

## Preventative Floor Care

- ❖ Use proper walk-off matting at all entries and where needed to trap soiling and contaminants before reaching the floor. Mats should be appropriate for soil load and weather conditions and have a non-staining backing. Clean matting often.
- ❖ Use floor protectors on all furniture legs. Floor glides should be at least 1 inch in diameter. Castors should have large diameter wheels with a smooth flat tread surface. Do not use narrow castors or those with a curved tread.
- ❖ When machine cleaning, always wet the pad before use on the floor. Never use a black or a build-up removal pad.
- ❖ Protect the floor from direct sunlight.

## Recommended Maintenance Products

- ❖ For a list of recommended maintenance products, please refer to our Maintenance Products Guide for CBC Flooring.

## Contact Information

For additional information, please call 800-446-5476  
Email: [tolifloors@cbcamerica.com](mailto:tolifloors@cbcamerica.com)  
[www.toli.com](http://www.toli.com)