



Lightwood RE & LL300 Maintenance

The following wax free maintenance program provides a natural, low-luster appearance and a savings in labor and chemical costs when compared with conventional cleaning and floor waxing systems. If preferred, Lightwood RE and LL300 can be successfully maintained using conventional acrylic floor finish.

Safety Precautions

- When performing any wet maintenance, always use wet floor signs and caution tape.
- Refer to each product's MSDS for use of personal protective equipment.



Newly Installed Floor Care

- Keep all foot traffic off the new floor for 12 hours.
- Keep furniture, fixtures and rolling traffic off the new floor for 48 hours.
- Use plywood or other boards when moving heavy objects across the floor.
- Remove adhesive residue with a clean white cloth dampened with mineral spirits. Do not use AFTA.
- Lightly damp mop the floor as needed.
- Wait 72 hours before wet washing and scrubbing the new floor. This will allow the adhesive to fully cure.

Routine Maintenance

- Sweep or dust mop to remove dirt and grit. Do not use treated dust mops.
- Add neutral pH cleaner to cool water following the manufacturer's instructions.
- Rinse the mop in clean water after each mopping pass to remove picked up soil.

Periodic Deep Cleaning

- Sweep or dust mop the floor to remove dirt and grit. Do not use treated dust mops.
- Add heavy duty cleaner to cool water following the manufacturer's instructions.
- Scrub with a 175-rpm machine or auto scrubber. Use a **blue or green pad**. Always wet the pad before use. **Never use a black or a build-up removal pad.**
- Remove the solution with a wet-dry vacuum or auto scrubber until the floor is dry and free of residue.
- Rinse the floor with clean water. Repeat the rinse process as necessary to remove all haze and residue.

Preventative Floor Care

- Proper matting system is recommended. Mats should be appropriate for soil load and weather conditions. Use mats with a non-staining backing.
- Floor protectors should be used on all furniture legs. The surface area of the floor glide should be no less than 1 inch in diameter.
- Protect the floor from direct sunlight.

Recommended Maintenance Products

- For a list of recommended maintenance products, please refer to our [Maintenance Product Guide](#) for TOLI Flooring.

Contact Information

For additional information, please call 1-800-446-5476
Email: support@toli.com
www.toli.com

